

# SINGLE PHASE

NUMBER OF CELLS	DC VOLTAGE	CHARGER MODEL	8 HR A.H RATING	MAX DC OUTPUT	AC AMP DRAW				CABINET STYLE	SUFFIX CODE
					120	208	240	480		
6	12	1NE6-240	170-240	48	20	10	12	6	S	LV OR HV
6	12	1NE6-380	251-380	76	16	9	8	4	S	LV OR HV
6	12	1NE6-450	381-450	90	18	10	9	5	S	LV OR HV
6	12	1NE6-510	451-510	102	20	11	10	5	S	LV OR HV
6	12	1NE6-600	511-600	120	24	14	12	6	S	LV OR HV
6	12	1NE6-660	601-660	132	N/A	18	16	8	M	HV
6	12	1NE6-725	661-725	145	N/A	18	16	8	M	HV
6	12	1NE6-750	726-750	150	N/A	18	16	8	M	HV
12	24	1NE12-240	180-240	48	16	9	8	4	S	LV OR HV
12	24	1NE12-255	241-255	51	16	9	8	4	S	LV OR HV
12	24	1NE12-380	256-380	76	20	11	10	5	S	LV OR HV
12	24	1NE12-450	381-450	90	N/A	18	16	8	S	HV
12	24	1NE12-510	451-510	102	N/A	22	20	10	M	HV
12	24	1NE12-600	511-600	120	N/A	27	24	12	M	HV
12	24	1NE12-725	601-725	145	N/A	33	30	15	M	HV
12	24	1NE12-750	601-750	150	N/A	33	30	15	M	HV
18	36	1NE18-240	170-240	48	N/A	16	14	7	M	HV
18	36	1NE18-380	241-380	76	N/A	24	22	11	M	HV
18	36	1NE18-450	381-450	90	N/A	31	28	14	M	HV
18	36	1NE18-510	451-510	102	N/A	33	30	15	M	HV
18	36	1NE18-600	511-600	120	N/A	35	32	16	M	HV
18	36	1NE18-680	601-680	136	N/A	36	34	17	M	HV
18	36	1NE18-750	601-750	150	N/A	39	36	18	M	HV
24	48	1NE24-240	170-240	48	N/A	18	16	8	M	HV
24	48	1NE24-380	251-380	76	N/A	32	30	15	M	HV
24	48	1NE24-450	381-450	90	N/A	33	30	15	M	HV
24	48	1NE24-510	451-510	102	N/A	35	34	17	M	HV
24	48	1NE24-600	511-600	120	N/A	39	36	18	M	HV

LV 120/208/240 A.C. VOLTS

HV 208/240/480 A.C. VOLTS