

THREE PHASE

NUMBER OF CELLS	DC VOLTAGE	CHARGER MODEL	8 HR A.H RATING	MAX DC OUTPUT	AC AMP DRAW				CABINET STYLE
					208	240	480	575	
6	12	3NE6-600	511-600	120	7	6	3	3	L
6	12	3NE6-725	601-725	145	9	8	4	3	L
6	12	3NE6-750	601-750	150	9	8	4	3	L
6	12	3NE6-900	751-900	180	14	12	6	5	L
6	12	3NE6-1050	901-1050	210	14	12	6	5	L
6	12	3NE6-1200	1051-1200	240	16	14	7	6	L
12	24	3NE12-380	251-380	76	10	8	4	3	L
12	24	3NE12-450	381-450	90	12	10	5	4	L
12	24	3NE12-510	451-510	102	14	12	6	5	L
12	24	3NE12-600	511-600	120	16	14	7	6	L
12	24	3NE12-725	601-725	145	18	16	8	7	L
12	24	3NE12-750	601-750	150	18	16	8	7	L
12	24	3NE12-900	751-900	180	23	20	10	9	L
12	224	3NE12-1050	901-1050	210	25	22	11	9	L
12	24	3NE12-1200	1051-1200	240	26	24	12	10	L
18	36	3NE18-380	251-380	76	16	14	7	6	L
18	36	3NE18-450	381-450	90	18	16	8	7	L
18	36	3NE18-510	451-510	102	21	18	9	8	L
18	36	3NE18-600	511-600	120	22	20	10	9	L
18	36	3NE18-725	601-725	145	27	24	12	10	L
18	36	3NE18-750	601-750	150	27	24	12	10	L
18	36	3NE18-900	751-900	180	35	32	16	14	L
18	36	3NE18-1050	901-1050	210	35	34	17	14	L
18	36	3NE18-1200	1051-1200	240	38	36	18	15	L
24	48	3NE24-380	251-380	76	22	20	10	9	L
24	48	3NE24-450	381-450	90	25	22	11	9	L
24	48	3NE24-510	451-510	102	27	24	12	10	L
24	48	3NE24-600	511-600	120	29	26	13	11	L
24	48	3NE24-725	601-725	145	33	30	15	13	L
24	48	3NE24-750	601-750	150	33	30	15	13	L
24	48	3NE24-900	751-900	180	42	36	18	15	L
24	48	3NE24-1050	901-1050	210	44	40	20	17	L

ALL CHARGERS ARE SET UP FOR 208/240/480 A.C. VOLTS
575 A.C. VOLTS SPECIAL ORDER